


MASS C-SERIES MONITORS

17" ANALOGUE



**User Controls:**

- Power - on/off
- On-screen Menu - on/off
- Select - scroll up/down
- Selection - increment/decrement

|  |              | Monitor Type                  | Size and Weight   | Aggregate Resolution            | Input Connections   | Display Adapter         |   |
|--|--------------|-------------------------------|---|---------------------------------|---|-------------------------|---|
|  | <b>C2H17</b> | Integrated dual screen LCDs   | 50cm x 74cm x 26cm (H x W x D) approx. 24.75 lbs (11.23 kg) | 2560 x 1024                     | 2 x 15-pin D-sub for analog RGB (0.7Vp-p 75 Ohms) Integrated cable. | Two outputs required.   | <b>Resolution:</b><br>640 x 400<br>720 x 400<br>640 x 480<br>800 x 600<br>832 x 624<br>1024 x 768<br>1280 x 1024<br><br>Approvals:<br>Tested to Comply With FCC Standards<br> |
|  | <b>C2V17</b> | Integrated dual screen LCDs   | 70cm x 37cm x 26cm (H x W x D) approx. 24.75 lbs (11.23 kg) | 1280 x 2048                     | 2 x 15-pin D-sub for analog RGB (0.7Vp-p 75 Ohms) Integrated cable. | Two outputs required.   |   |
|  | <b>C3H17</b> | Integrated triple screen LCDs | 50cm x 111cm x 26cm (H x W x D) approx. 33 lbs (14.97 kg)   | 3840 x 1024                     | 3 x 15-pin D-sub for analog RGB (0.7Vp-p 75 Ohms) Integrated cable. | Three outputs required. |   |
|  | <b>C3P17</b> | Integrated triple screen LCDs | 81cm x 74cm x 26cm (H x W x D) approx. 34 lbs (15.42 kg)    | 1280 x 1024<br>+<br>2560 x 1024 | 3 x 15-pin D-sub for analog RGB (0.7Vp-p 75 Ohms) Integrated cable. | Three outputs required. |   |
|  | <b>C4P17</b> | Integrated quad screen LCDs   | 81cm x 111cm x 26cm (H x W x D) approx. 44.5 lbs (20.18 kg) | 1280 x 1024<br>+<br>3840 x 1024 | 4 x 15-pin D-sub for analog RGB (0.7Vp-p 75 Ohms) Integrated cable. | Four outputs required.  |   |
|  | <b>C4Q17</b> | Integrated quad screen LCDs   | 81cm x 74cm x 33cm (H x W x D) approx. 44.5 lbs (20.18 kg)  | 2560 x 2048                     | 4 x 15-pin D-sub for analog RGB (0.7Vp-p 75 Ohms) Integrated cable. | Four outputs required.  |   |
|  |              | Power Requirements            | Line Voltage: 110 to 220 VAC, 50 -60 Hz                     |                                 |   |                         |   |
|  |              | Power                         | 30 W (operating) per display panel                          |                                 |   |                         |   |
|  |              | Pixel Pitch (mm)              | 0.264 (H) x 0.264 (V)                                       |                                 |   |                         |   |
|  |              | Color Depth                   | 16.2 million colors   |                                 |   |                         |   |
|  |              | Viewing Angle                 | H +75°/-75°, V +75°/-60° typical                            |                                 |   |                         |   |
|  |              | Brightness                    | 300 cd/m <sup>2</sup>                                       |                                 |   |                         |   |
|  |              | Contrast Ratio                | 700:1 typical   |                                 |   |                         |   |
|  |              | Response Time                 | 8 ms  |                                 |   |                         |   |
|  |              | Screen Size and Type          | 17" Flat panel diagonal display / TFT active matrix         |                                 |   |                         |   |
|  |              | Surface Treatment             | Anti-glare and hard coatings 3H                             |                                 |   |                         |   |

**MASS C-SERIES, A CONFIGURABLE SYSTEM FOR INFORMATION ERGONOMICS™**



MASS Engineered Design Inc.

info@massmultiples.com | www.massmultiples.com | 1-888-603-9858